



DXS® DRIVE XCHANGE SYSTEM™ IMPACT SOCKETS

Never lose power from worn sockets and square drive anvils with Drive Xchange System™ Sockets.

Enjoy easier access into tight spaces with up to 3/4" shorter tool length when used with Ingersoll Rand® DXS® impact wrenches. DXS® direct drive sockets fit tighter and have more load bearing surface compared to traditional square drives to deliver up to 15% better torque transfer and 20% longer wear life.

MORE

TORQUE POWER TRANSFER
ACCESS WITH SHORTER LENGTH
VALUE WITH LONGER WEAR LIFE



FEATURES

- Ball nose retention pin for quick, tool-free installation and removal
- High visibility laser etched markings to easily identify the size you need
- Sets include EVA foam shadow board organizer for storage
- Backed by a lifetime limited warranty for peace of mind with proven reliability
- Made from chrome molybdenum (CR-MO) alloy steel for exceptional strength and durability

US and International Patents Pending. DXS® Registered Trademark of Ingersoll Rand. ©2024 Ingersoll Rand.

METRIC DEEP & STANDARD SOCKETS

Deep Single Sockets

DXS2SM12L	12 MM
DXS2SM13L	13 MM
DXS2SM14L	14 MM
DXS2SM15L	15 MM
DXS2SM16L	16 MM
DXS2SM17L	17 MM
DXS2SM18L	18 MM
DXS2SM19L	19 MM

DXS2SM21L	21 MM
DXS2SM22L	22 MM
DXS2SM24L	24 MM
DXS2SM27L	27 MM
DXS2SM30L	30 MM
DXS2SM32L	32 MM
DXS2SM33L	33 MM



DXSK2M15L - DXS2™ Drive Deep Metric Impact Socket Set, 15-Piece

DXSK2M15 - DXS2™ Drive Standard Metric Impact Socket Set, 15-Piece

Standard Single Sockets

DXS2SM12	12 MM
DXS2SM13	13 MM
DXS2SM14	14 MM
DXS2SM15	15 MM
DXS2SM16	16 MM
DXS2SM17	17 MM
DXS2SM18	18 MM
DXS2SM19	19 MM

DXS2SM21	21 MM
DXS2SM22	22 MM
DXS2SM24	24 MM
DXS2SM27	27 MM
DXS2SM30	30 MM
DXS2SM32	32 MM
DXS2SM33	33 MM



SAE (IMPERIAL) DEEP & STANDARD SOCKETS

Deep Single Sockets

DXS2SH716L	7/16"
DXS2SH12L	1/2"
DXS2SH916L	9/16"
DXS2SH58L	5/8"
DXS2SH1116L	11/16"
DXS2SH34L	3/4"
DXS2SH1316L	13/16"

DXS2SH78L	7/8"
DXS2SH1516L	15/16"
DXS2SH1L	1"
DXS2SH1-116L	1-1/16"
DXS2SH1-18L	1-1/8"
DXS2SH1-316L	1-3/16"
DXS2SH1-14L	1-1/4"



DXSK2H14L - DXS2™ Drive Hex Deep SAE (Imperial) Impact Socket Set, 14-Piece

DXSK2H14 - DXS2™ Drive Standard SAE (Imperial) Impact Socket Set, 14-Piece

Standard Single Sockets

DXS2SH716	7/16"
DXS2SH12	1/2"
DXS2SH916	9/16"
DXS2SH58	5/8"
DXS2SH1116	11/16"
DXS2SH34	3/4"
DXS2SH1316	13/16"

DXS2SH78	7/8"
DXS2SH1516	15/16"
DXS2SH1	1"
DXS2SH1-116	1-1/16"
DXS2SH1-18	1-1/8"
DXS2SH1-316	1-3/16"
DXS2SH1-14	1-1/4"





Ingersoll Rand



**WHY OUR NEW
PATENTED IMPACT
WRENCH IS THE BEST
CHOICE**

POWERFUL

Industry's most compact high torque impact wrench delivering 1,500 ft-lbs of breakaway torque while weighing less than 4.4 lbs and in a length under 7.3"

VERSATILE

Interchangeable drives can quickly configure this tool for the job without losing power, increasing size or needing more tools

DURABLE

More legendary durability from an unyielding titanium hammer case and a patented direct hammer lubrication system



**2236Q TiMAX
IMPACT WRENCH**

DXS² Drive Xchange System™

INTERCHANGEABLE GAME-CHANGER

Ingersoll Rand® 2236 MAX Series 1/2" Impact Wrench



irtools.com/DXS

Introducing the Ingersoll Rand® 2236 MAX Series.

Versatility meets power in the new Ingersoll Rand 1/2" pneumatic impact wrench. The patented* Drive Xchange System™ lets you switch out anvils without clunky adapters that drain your tool's power.



AVAILABLE CONFIGURATIONS



2236QTIMAX
Standard Friction Ring Anvil



2236OPTIMAX
Standard Pin Anvil



2236QTIMAX-2
2" Extended Friction Ring Anvil

Titanium Hammer Case
Lightweight with unyielding durability

Longer Life
Reliability from a patented direct greasing design

200 ft-lbs More Powerful
1,500 Ft-lbs of Nut busting Torque from a patented motor design**

Quieter
4 decibels quieter from a patented motor design***

More Versatility
Patented DXS Drive Xchange System™



Interchangeable anvils including:
3/8", 1/2", and 3/4 inch drive options and five lengths from 2 to 10 inches

More Compact
1/4" shorter length from a patented motor

Better Health and Ergonomics
Reduced fatigue from lower weight, better balance

AVAILABLE DRIVE SIZES

AK33H
3/8", 1/2", 3/4"



AK43H
3/4", 1/2 x 2", 1/2 x 4"



* Global Patents Pending
** Compared to IR 2235QTIMAX
*** Compared to IR 2235TIMAX

Model	Drive Size	Breakaway Torque ft-lbs (Nm)	Impact Per Minute (BPM)	MAX Free Speed (RPM)	Impacting Sound Level dB(A)	Weight lbs (kg)	Length in (mm)	Air Inlet (NPTF/NPT)	Min Hose Size in (mm)
2236QTIMAX	1/2" Standard Anvil	1500 (2034)	1350	7500	94.2	4.4 (1.99)	7.36 (187)	1/4"	3/8 (10)
2236QTIMAX-2	1/2 x 2" Extended Anvil	1500 (2034)	1350	7500	94.2	4.6 (2.1)	9.37 (238)	1/4"	3/8 (10)
2236OPTIMAX	1/2" Pin Anvil	1500 (2034)	1350	7500	94.2	4.4 (1.99)	7.36 (187)	1/4"	3/8 (10)

DRIVE KITS

AK32H 2-pc Kit Includes: 3/8", 1/2" Std
AK33H 3-pc Kit Includes: 3/8", 1/2" Std, 3/4" Std
AK42H 2-pc Kit Includes: 1/2 x 2" Ext, 3/4" Std
AK43H 3-pc Kit Includes: 1/2 x 2" Ext, 1/2 x 4" Ext, 3/4" Std

AK62H 2-pc Kit Includes: 1/2" Std, 3/4" Std
EAK62H 2-pc Kit Includes: 3/4" Std, 3/4 x 6" Ext
EAK44H 4-pc Kit Includes: 1/2 x 4", 6", 8", 10" Ext



Learn more at www.ingersollrand.com

Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency.

©2023 Ingersoll Rand PTL_279_00_2023_2236QTIMAX_ImpactWrench_Flyer